



The all new KATKO Terminal Block range was developed after profound scientific research. The findings were combined with KATKO's superior production know-how which resulted in a range that is of the highest quality, has exceptional performance, and is absolutely reliable.

The range is certified according to IEC 61238-1 Class A standard with also the relevant mechanical tests.

TERMINAL BLOCKS

For Al and Cu cables

- IEC 61238-1:2003, Class A
- Advanced DIN rail mounting
- Mechanically very strong
- Durable laser markings
- Suitable for Al/Cu cables 2,5 - 240 mm²



Type	EAN code	Un (V)	In (Al) (A)	In (Cu) (A)	Al/Cu mm ²	Torque Al/Cu	Key size	Mounting	Weight kg
	6419410...					(Nm)			
KL 1x50	...378250					5 (2.5 - 10 mm ²)			
KL 1x50N	...378267	1000	160	160	2.5 - 50		Hex 5	Screw / DIN	0.060
KL 1x50PE	...378274					10 (16 - 50 mm ²)			
KL 2x50	...378281					5 (2.5 - 10 mm ²)			
KL 2x50N	...378298	1000	160	320	2.5 - 50		Hex 5	Screw / DIN	0.104
KL 2x50PE	...378304					10 (16 - 50 mm ²)			
KL 1x95	...378311					12 (16 - 50 mm ²)			
KL 1x95N	...378328	1000	200	245	16 - 95		Hex 6	Screw / DIN	0.096
KL 1x95PE	...378335					22 (70 - 95 mm ²)			
KL 2x95	...378342					12 (16 - 50 mm ²)			
KL 2x95N	...378359	1000	400	490	16 - 95		Hex 6	Screw / DIN	0.169
KL 2x95PE	...378366					22 (70 - 95 mm ²)			
KL 1x150	...378373					12 (25 - 50 mm ²)			
KL 1x150N	...378380	1000	250	320	25 - 150	22 (70 - 95 mm ²)	Hex 6	Screw / DIN	0.181
KL 1x150PE	...378397					38 (120 - 150 mm ²)			
KL 2x150	...378403					12 (25 - 50 mm ²)			
KL 2x150N	...378410	1000	500	640	25 - 150	22 (70 - 95 mm ²)	Hex 6	Screw / DIN	0.317
KL 2x150PE	...378427					38 (120 - 150 mm ²)			
KL 1x240	...378434					25 (35 - 120 mm ²)			
KL 1x240N	...378441	1000	315	425	35 - 240		Hex 8	Screw / DIN	0.293
KL 1x240PE	...378458					55 (150 - 240 mm ²)			
KL 2x240	...378465					25 (35 - 120 mm ²)			
KL 2x240N	...378472	1000	630	850	35 - 240		Hex 8	Screw / DIN	0.522
KL 2x240PE	...378489					55 (150 - 240 mm ²)			

- = Grey, N = Blue, PE = Yellow/Green