


Nimi: **Kojerasia**
Irtonysärasia

Tyyppi: AU3.2
EAN: 6410011523643
Snro: 1152364

Kuvaus: Rasian sivuilla on 5 kpl nysäihioita, joista kaksi on samalla sivulla vierekkäin. Pohjaan voidaan liittää kaksi pohjanysää. Rasiat yhdistetään toisiinsa yhdyskappaleella PMR474. Valmistettu halogeenittomasta materiaalista (IEC/61249-2-21) ja täyttää hehkulankatestin vaatimukset standardin IEC/EN60670: 2005 (850 °C) mukaan.

Pakkaus: 100
Yksikkö: KPL


Tekniset tiedot
Sähkösuureet

Käyttöjännite 400 V

Lämpöolosuhteet

Käyttölämpötila -25 ... 90 °C

ETIM

ETIM 5.0 EC002601 (EC002601)

ETIM 6.0 EC002601 (EC002601)

ETIM 6

Mounting method Flush mounted (plaster)
Shape Round
Construction type Device connection box (round/square)
Model Single
Provided with revolving ring
Can be coupled 1
Equipped with None
Diameter 71 mm
Length
Width
Depth 47 mm
Internal depth 45 mm



TUOTEKORTTI

25.10.2017

AU3.2

2/2

For number of electric fittings	1
Mounting switching equipment	Screwing
With screws	1
Housing feed-through by break-out opening	
Housing feed-through by seal membrane	
Housing feed-through by nozzle	
Housing feed-through by step membrane	
For tubediameter	20/25 mm
Suitable for cable diameter	
Pipe locking	1
Pipe locking optional	
Inlet from the rear	1
Number of inlets	
Number of included spouts	
Material	Plastic
Halogen free	1
Surface protection	Untreated
Colour	White
Degree of protection (IP)	Other
Cover	Not transparent
Cover attachment	Snapped on
Sealable	
Circuit integrity	None
With screening	
Wind proof	
Max. conductor cross section	0 mm ²
Number of poles of the clamp	
Clamp position fixed	
Luminaire hook mounting	
Nozzle	None
With nail lugs	1
Special application	