



PHE3S2 60 110 S (767 980)

■ Transport case included




Figure without obligation

Kit includes:			
Pos. No.	Part No.	Pos. No.	Part No.
1	766 924	13	767 965
2	766 923	14	766 352
3	767 771	15	766 359
4	767 772	16	766 358
5	767 764	17	766 114
6	767 972	18	766 115
7	767 974	19	766 128
8	767 734	20	766 120
9	767 726	21	766 889
10	767 732	22	766 996
11	767 735	23	766 998
12	767 963		

For more detailed information on these products, see Accessory chapter

Type	PHE3S2 60 110 S
Part No.	767 980
Nominal voltage (U _N)	60 ... 110 kV
Type of voltage	a.c.
Frequency	50 Hz
Category	S
Total length (l _o)	2980 mm
Insertion depth (l _o)	880 mm
Standard	EN/IEC 61243-1 (DIN VDE 0682-411)
Temperature range	-25 °C ... +55 °C, climatic category N
Design	Complete
For use in wet weather conditions	Yes
For	Indoor and outdoor installations
Application	Switchgear installations and overhead lines
Design	Single-pole
Indication	Acoustic and visual
Self-testing element	Yes
Material (test electrode)	Copper alloy/gal Sn
Material (test prod)	Glass-fibre reinforced epoxy resin tube
Material (indicator)	Plastic, fully insulated
Material (insulating stick)	Glass-fibre reinforced polyester tube
Weight	5,98 kg
Customs tariff number	90303310
GTIN	4013364125926
PU	1 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.