



Note:
- Drawings Not To Scale
- Drawings Subject to Change Without Notice
- Dimensions are inches next to [Millimeters]

Part No.:
LP1K0910BD



Schneider Electric United States
North American Division
Boston One Campus
800 Federal Street
Andover, MA 01810, USA
Phone: +1 8773425173
Email: CCC@us.schneider-electric.com

Rating: 600V / 9A
UL File/CCN: E164353 / NKCR
CSA File: LR43364 3211 03
Meets Standards: IEC 60647-1-1
Weight: 0.40 lb (0.18 kg)
Termination Method: Screw Clamp
Wire Size: Power: #12 - #18 AWG
Control: #12 - #18 AWG
Terminal torque: Power: 7 lb-in (0.8 Nm)
Control: 7 lb-in (0.8 Nm)
Mounting Hwd.: 35mm DIN Rail, 4mm screw

Technical Information:

Description: TeSys K Non-reversing Contactor
Type: TeSys K IEC Contactor - 9A - 24Vdc Coil
Voltages Code: BD at 24VDC

Coil Consumption: Inrush 3 W
Sealed 3W

Single Phase		Three Phase			
115V	230V	200V	230V	460V	575V
0.5 HP	1.5 HP	2 HP	3 HP	5 HP	5 HP

Specification: