

PRODUCT DATASHEETENDURA BEAM GAP wall updown GU10

ENDURA BEAM | GU10 socketed luminaires with classic shape and light outlet up and down



AREAS OF APPLICATION

- Building facades
- Entrance lighting
- Patios, balconies
- Pathway lighting
- Driveways

PRODUCT BENEFITS

- High flexibility in the choice of the light source thanks to GU10 base
- Easy and quick installation

PRODUCT FEATURES

- Indirect illumination
- Housing material: aluminum
- Housing color: RAL 7016
- Type of protection: IP44



TECHNICAL DATA


Electrical data

Operating mode	Mains voltage
Nominal voltage	220240 V
Mains frequency	50/60 Hz

Luminaire control gear data

ECG - Dimmable	No
----------------	----

Dimensions & weight



Length	104.0 mm
Width	92.0 mm
Height	233.0 mm
Product weight	844.00 g

Colors & materials

Body material	Aluminum
Product color	Dark gray
Housing color	Dark gray
Cover material	Glass

Temperatures & operating conditions

Ambient temperature range	-20+40 °C

Additional product data

Mounting type	Surface	
Mounting location	Wall	
Product remark	Maximum bulb wattage: 2 x 35 W	

Capabilities

Dimmable	No	
Type of connection	Terminal, 3-Pole (L, N, PE)	
Holder designation	GU10	

Certificates & standards

Protection class	1
Type of protection	IP44
Standards	CE/EAC/RoHS/REACH

EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included
- No light sources included

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075554559	Folding carton box 1	100 mm x 110 mm x 240 mm	914.00 g	2.64 dm ³
4058075554566	Shipping carton box 4	245 mm x 220 mm x 265 mm	4025.00 g	14.28 dm³

 The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.