


## MHS-LSZH

### Halogen free indoor cable



**APPLICATION** Indoor cable for access networks

<b>CONSTRUCTION</b>	Conductor	Annealed, tinned copper wire
	Insulation	Solid PE
	Twinning	Two insulated conductors in a pair
	Lay-up	Stranded into units
	Ground wire	Annealed, tinned copper wire
	Screen	Plastic-aluminium foil
	Sheath	Grey HFFR-compound

SSTL code	Type MHS-LSZH	Draka code	Diameter mm	Sheath thickness mm	Mass kg/km	Delivery length m	Drum/ packaging
0202402	1x4x0.5	L712910	5.1	1.0	28	1000	K5
0202404	1x4x0.5	L715970	5.1	1.0	28	100	coil
0202406	1x4x0.5	L715987	5.1	1.0	28	300	coil
0202408	3x2x0.5	L712447	5.8	1.0	36	1000	K6
0202410	3x2x0.5	L715988	5.8	1.0	36	200	coil
0202412	5x2x0.5	L712907	6.7	1.0	49	1000	K6
0202414	5x2x0.5	L715989	6.7	1.0	49	150	coil
0202416	10x2x0.5	L712446	7.8	1.0	73	1000	K6
0202418	10x2x0.5	L715990	7.8	1.0	73	200	coil
0202420	20x2x0.5	L712908	9.2	1.0	120	1000	K7
0202422	20x2x0.5	L715991	9.2	1.0	120	150	coil
0202424	30x2x0.5	L712909	11.0	1.1	170	1000	K8
0202426	50x2x0.5	L709021	14.0	1.1	270	1000	K9
0202428	100x2x0.5	L715001	19.5	1.2	505	1000	K12