

FieldLink®

Industrial Ethernet Cat 5e ES



Design

Wire:

Stranded tinned wire 7 X 0.25
Insulation of Polyethylene (PE)

ø 0.75 mm
ø 1.5 mm

Core:

Filler as central element
1. layer: 4 wires 2Y 0.75/1.5 LI
Sequence of colors: WH-YE-BU-OG
Plastic tape, overlapped
Inner jacket: Thermoplastic copolymer (FRNC)
Alulamine foil overlapped
Shield braiding of tinned copper wires 0.13 mm dia
Coverage about 85%

ø 3.9 mm

ø 4.7 mm

Jacket:

Polyurethane (PUR) GN
Wall thickness about 0.9 mm

ø (6.5 ±0.2) mm

Printing: "sequential length in metres" LEONI L INDUSTRIAL ETHERNET TRAILING CABLE * PROFINET
Type C ES CAT5 PLUS * 22AWG (SHIELDED) (UL) E119100 CMX 75°C VERIFIED (UL) CAT 5E
PATCH CABLE FRNC * "year/internal order number"

Textintervals about 1000 mm

Electrical data at 20°C

Loop resistance	≤	120	Ohm/km
Signal run time	≤	5.3	ns/m
Insulation resistance	≥	500	MΩ·km
Characteristic impedance		(100 ±15)	Ohm
Capacitance (1 kHz)	nom.	52	nF/km
UL-Rating		600	V
Surface transfer impedance	≤	20	mΩ/m
Test voltage (wire/wire/screen rms 50Hz 1min)	=	2000	V

Near-end crosstalk attenuation

Frequency (MHz)	1	4	10	16	20	31.25	62.5	100
typ. value (dB - 100m)	80	76	70	65	63	60	55	50

Attenuation

Frequency (MHz)	1	4	10	16	20	31.25	62.5	100
typ. value (dB/100m) (dB/100ft)	2,1 (0,6)	4 (1,2)	6,3 (1,9)	8 (2,4)	9 (2,7)	11,4 (3,5)	16,5 (5,0)	21,3 (6,5)

The electrical requirements similar to EN 50288-2-1

Mechanical and thermal characteristics

Conductor/Screen material acc. to DIN EN 13602 Cu-ETP-A...-B

Insulating material acc. to DIN EN 50290-2-23 (VDE 0819), table L/MD (HD 624.3)

Jacket material acc. F45052-F5100 (similar to DIN VDE 0282)

Oil resistant acc. to DIN EN 60811-404 (7x24h/90°C)

Flame retardant acc. to IEC 60332-1-2

UL File E119100 Vol.1 Sec. 13 Page 1

UL File E352715 Vol.1 Sec. 1 Page 3 Verified CAT 5E

Other characteristics:

RoHS compliant (Directive 2011/65/EC)

Sunlight resistant acc. to UL 2556 Sec. 4.2.8.5 (720h)

Flame retardant acc. to ECE-R 118 Amendment 02, Para. 6.2.6 with the ISO 6722- 1:2012 Para. 12

Halogen free

Tensile strength $\leq 150N$

Trailing cable for following requirements

- 3 million bending cycles
- diameter 200 mm
- at a speed of 4 m/s
- acceleration 4 m/s²

Permissible temperature range : -40°C up to +70°C

During laying : -20°C up to +60°C

Transport temperature range : -50°C up to +70°C

Min. bending radius allowed : repeated 8X \varnothing , single 4X \varnothing

Weight about : 61 Kg/km (40,9 lb/1000ft)

Application:

Trailing cable

Designation of order:

L45467-J17-B18 / 202283

2YH(ST)C11Y 2X2X0.75/1.5-100 LI GN VZN FRNC

2000 m (6562 ft) on non-returnable reel