

Accessories - "weatherproof" for outdoor installation

LDM 32 G



- Cable feed-through
- for knockouts in the rear wall M 32



- sealing range: Ø 12-24 mm
- bore-hole: Ø 32.5 mm
- wall thickness 0,5-4,5 mm
- for indoor - normal environment and (or) protected outdoor installation
- ambient temperature - 25 °C to + 55 °C
- Glow wire test IEC 60695-2-11: 750 °C
- degree of protection: IP 66 / IP 67
- colour: grey, RAL 7035

material	TPE (-25° to +80°C)
weight	0,0072 kg

Operating and ambient conditions

Application area	Suitable for indoor installation and outdoor installation, protected against weather influences
Ambient temperature	Average value over 24 hours + 55 °C Maximum value + 70 °C Minimum value - 25 °C
Fire protection in the event of internal faults	Demands placed on electrical devices from standards and laws Minimum requirements - Glow wire test in accordance with IEC 60695-2-11: - 650° C for boxes and cable glands
Burning behaviour	Glow wire test IEC 60695-2-11: UL Subject 94: HB flame-retardant self-extinguishing
Toxic behaviour	halogen-free silicone-free "halogen-free" in accordance with the examination of the cables and insulated wires - corrosiveness of fumes - as per IEC 60754-2
Note:	For material properties see technical data.