

Joint closure NC-412 / 3



Characteristics:

- Designed for direct buried, manhole or pole/wall mount applications
- Capacity: 12 fibre splices
- One inlet Ø 22,9 mm for max. 3 drop cables
- Inlet is sealed with a 3-sleeve heat shrink
- Includes a fixed splice tray for 12 splices.
- Dimensions: Length 250 mm, closure Ø 76 mm, flange Ø 114 mm
- Material: Acid-proof stainless steel
- Tightness: IP 67

Basic assembly:

- Inner part with fixed splice tray and lid, cover part, rubber seal and bolts
- Heat shrink with 3 sleeves for max. 3 cables. Unused sleeves are easy to plug
- Grounding clip for 16 mm² grounding wire (grounding wire not included)
- Mounting and grounding parts for incoming cables
- Cable ties
- Splice protection sleeves for 12 single fibre splices
- Holder for 12 splice protection sleeves
- Dehumidifier

Accessories:

- Pole/wall mount stand, sold separately

©Nestor Cables Ltd. 2016.

The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the prior written consent of Nestor Cables Ltd. The information is believed to be correct at the time of issue. Nestor Cables Ltd. reserves the right to amend this specification without notice. This specification is not contractually valid unless specifically authorized by Nestor Cables Ltd.