

TWIN-WALL OUTLET SAT-IF

- Twin-wall outlet for 2-wire-SAT-IF application
- With DC pass
- Including cover plate and frame



| Type | Frequency range | STD 2400 |
|----------------------------|-----------------|--|
| Item No. | | 10161174 |
| | | |
| Description | | terminal-twin wall outlet |
| Attenuation | | |
| TV OUT (IEC-male) dB | 85-862 MHz | 1.0 - 2.0 |
| RF OUT (IEC-female) dB | 87.5-862 MHz | 1.0 - 2.0 |
| 2x SAT OUT (F-female) dB | 950-2200 MHz | 4.0 - 6.5 |
| DC pass | | 12 V =, max. 500 mA (over SAT-IF-connectors) |

ACCESSORIES FOR ANTENNA WALL OUTLETS

| Type | AD 1 | AD 3 SET | AP 1 |
|-------------|--|--|--------------|
| | | | |
| Item No.. | 57001580 | 57001452 | 10161348 |
| Description | special cover KBW 1-hole, incl. security screw | Set with cover plate and frame for 3-hole outlets | frame |
| Dimensions | mm 55 x 55 x 3 | 76 x 76 x 8 / 76 x 76 x 32 | 76 x 76 x 32 |

| Type | R 75 | R 75 DC |
|-----------------|-----------------------------|-----------------------------------|
| | | |
| Item No. | 57000813 | 57000990 |
| Description | terminal resistor | terminal resistor DC isolated |
| Frequency range | MHz 0 – 2200 | 10 – 2200 |
| Load | 75 Ohm | 75 Ohm |
| Application | for DC isolated walloutlets | for SAT-wall outlets with DC pass |